

## Description

The 24V Eco LED Bars, just like our 24V LED Bars, aims to create a new lighting concept and considerably reduce even more energy consumptions than previous versions.

Color temperature tolerance of 3 SDCM MacAdam ellipses, defined by ANSI C78.377:2011

Energy Efficiency Class: A+ (EU 874-2012)

LEDs are classified as Risk Group 1 according standard EN62471 Photobiological Safety of Lamps and Lamp Systems.

Our polycarbonate lens meets the standard for Food contact FDA 21CFR 177.1580 and (EU) No. 10/2011 for European Union

A great flexibility of sizes, (10cm to 220cm) allows to adapt the sizes and luminosity to each project.

With easy installation, allows the use of individual bars for each of the sizes and or join several bars in a continuous line so that the space is suitably illuminated.

## Product Benefits

Lumen depreciation / useful lifetime - Have an average useful lifetime of 60.000 hours on L70;

Energy savings - Above 75% of predicted savings. High efficiency, low energy consumption and works on low voltage;

New lamp design possibilities;

Less ambiental impact throughout it's life cycle.

The LED efficiency increase allows us to re-manufacture the LED Bars.

That increase in efficiency and more lumens per watt allows us to re-manufacture the LED Bars in the future, if it is profitable luminotecnically and financially;

Repair possibility of LED Bar lamps during it's useful lifetime;

The re-manufacture and repair of LED Bar lamps, grants us an higher balance in investments and a better commitment with the environment.

## Technical Features:

Power source	Class II constant voltage external LED drive power supply
Voltage	24 ± 3 V DC
Current	450 mA
Power	10.8 ± 0.5W
Useful Lifetime	60.000 hours (L70 - 55°C @ 65%RH) *
Beam angle	120 ± 5° **
Field angle	Clear: 135 ± 5° Frost: 195 ± 5° ***
Nr of LEDs	90 - SMD
Working Temp.	-20 to 40 °C
Isolation	Class III
Protection degree	IP42
Lumen maintenance	LM80 (Report available: <a href="#">LM-80 9000hrs</a> )
Certificate	CE / RoHs

\*Luminosity depreciation based on L70.

\*\*Beam angle: 50% of maximum lum.

\*\*\*Field angle: 10% of maximum lum.

## Light Technical Data:

Reference	Description	Luminous flux (Lm)*	Efficiency (Lm/W)	Color Temp. (K)**	Color	CRI >	Lens Type
11112532151	LLED Barra 24V 115 WW303 HE ECO DL Clear	1028	95	3045 ± 84	Warm	80	Clear
11112532152	LLED Barra 24V 115 WW303 HE ECO DL Frost	850	79	3045 ± 84	Warm	80	Frost
11112534151	LLED Barra 24V 115 NW403 HE ECO DL Clear	1075	100	3986 ± 144	Neutral	80	Clear
11112534152	LLED Barra 24V 115 NW403 HE ECO DL Frost	890	82	3986 ± 144	Neutral	80	Frost
11112525151	LLED Barra 24V 115 CW503 ECO DL Clear	1028	95	5029 ± 186	Cool	80	Clear
11112525152	LLED Barra 24V 115 CW503 ECO DL Frost	850	79	5029 ± 186	Cool	80	Frost
11112536151	LLED Barra 24V 115 CW573 HE ECO DL Clear	1075	100	5668 ± 207	Cool	80	Clear
11112536152	LLED Barra 24V 115 CW573 HE ECO DL Frost	890	82	5668 ± 207	Cool	80	Frost
11112527151	LLED Barra 24V 115 CW653 ECO DL Clear	1028	95	6536 ± 279	Cool	80	Clear
11112527152	LLED Barra 24V 115 CW653 ECO DL Frost	850	79	6536 ± 279	Cool	80	Frost

\* Luminous flux ± 7.5%

\*\* Other color temperatures available upon request



## References Code:

The last six numbers are used to choose the options you desire.

### XXYYZZ

The XX refers to the body option.

The YY corresponds if the product have connectors.

The ZZ refers to the cable type.

### XX

Natural Aluminum | Ref:...01YYZZ

Chocolate Aluminum | Ref:...03YYZZ

White Aluminum | Ref:...02YYZZ

### YY



(STOPO) Top Input cable

Ref:...XX01ZZ



(1C2P STOPO) Top Input cable output connector

Ref:...XX08ZZ



(1C2P) Male connector input


Ref:...XX04ZZ



(1C2P) Male connector input female connector output


Ref:...XX06ZZ

### ZZ




(-)

Ref:...XXYY00




(ASQC2)

Ref:...XXYY27



(DCJ)


Ref:...XXYY25



(DC24)

Ref:...XXYY42

## Dimensions




A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)
15	12	20	17	1144	1160	1129

## CCT (Color temperature)

Color temperature tolerance of 3 SDCM MacAdam ellipses, defined by ANSI C78.377:2011

## Cool white 6500K 3SDCM



### Photometric Parameters

EEL: 0.15 Energy Efficiency Class: A+ (EU 874-2012)

### CIE Colorimetric Parameters

Chromaticity coordinates:  $x=0.3154$   $y=0.3330$   $u(u')=0.1982$   $v=0.3139$   $v'=0.4709$

CCT:  $T_c=6338K$  ( $duv=0.00393$ ) CRI:  $R_a=87.4$  Color Ratio:  $R=0.140$   $G=0.803$   $B=0.057$

## Options

We provide all professionals and non professionals with a huge installation flexibility of our LED Bars.


Give your lighting area a new look and design with 3 available finishing colours for the body lamp and 2 types of lens polycarbonate.

Fixed or rotating docking.


Huge connection flexibility.

### Options: Body


We provide 3 finishing jobs for the bar body, that allows for a new look and design when using our LED bars.




Natural Aluminum



Chocolate Aluminum



White Aluminum



Polycarbonate

### Options: Cover

We provide 2 types of polycarbonate, clear and frost.




Clear cover




Frost cover

### Options: Metallic Fixture


We provide 4 types of docking, rotating so the bar can be oriented, fixed @ 45°, fixed @ 180° and fixed @ 180° with extra 45°. Available in PVC, fixing at 180°, 45° and on corners.




Clip 180° (45° extra)



180° Fix clip




45° Fix clip




Rotating clip

### Options: Pvc Fixture


We provide 4 types of docking, rotating so the bar can be oriented, fixed @ 45°, fixed @ 180° and fixed @ 180° with extra 45°. Available in PVC, fixing at 180°, 45° and on corners.



180° PVC clip



45° PVC clip



Corner PVC clip

## Options: Connection

For greater installation flexibility of our LED bars, we provide bars with the following characteristics:

Cable input, connector input.

Cable input and connector output and connector input and connector output, so other LED bars can be interconnected.



Top Input cable  
(STopo)




Top Input cable output connector  
(1C2P STopo)



Male connector input  
(1C2P)



Male connector input female connector output  
(2C2P)



Top Input cable with ASQC2 connector  
(ASQC2)