

## Description



The Eco<sup>2</sup> LED Bars, just like our 3s Led Bars or ECO, aims to create a new lighting concept and considerably reduce even more energy consumptions than previous versions.

Color temperature tolerance of 3 SDCM MacAdam ellipses, defined by ANSI C78.377:2011 LEDs are classified as Risk Group 1 according standard EN62471.

Photobiological Safety of Lamps and Lamp Systems. Our polycarbonate lent meets the standard for Food contact FDA 21CFR 177.1580 and (EU) No. 10/2011 for European Union.

By using these ECO2 Bars, you can keep the lighting area with high savings regarding electric energy consumption (Kwh) with a low investment.

Huge flexibility size(90-2250mm) allows size and lighting composition for each project.

Easy to install, allows the use of single bars for each sizes, or join several continuous bars so that the lighting space is suitable.

An higher lifetime is achieved comparing with traditional fluorescent lamps.

## Product Benefits

Lumen depreciation / useful lifetime - Have an average useful lifetime of 60.000 hours on L70;

Energy savings - Above 90% of predicted savings. High efficiency;

High efficiency, low energy consumption and low working voltage;

New lamp design possibilities;

High lighting efficiency;

Less environmental impact throughout it's life cycle.

The LED efficiency increase, more lumen per watt, allows us to re-manufacture the LED Bars in the future, if it is profitable luminotechnical and financially;

Repair possibility of LED Bar lamps during it's useful lifetime;

The re-manufacture and repair of LED Bar lamps, grants us an higher balance in investments and a better commitment with the environment.

## Technical Features:

|                   |   |
|-------------------|---|
| Power source      | Class II constant voltage external LED drive power supply |
| Voltage           | 24 ± 3 V DC   |
| Current           | 119 mA  |
| Power             | 2.9 ± 0.2W  |
| Useful Lifetime   | 60.000 hours (L70 - 55°C @ 65%H) *                        |
| Beam angle        | 120 ± 5° **   |
| Field angle       | Clear: 135 ± 5° Frost: 195 ± 5° ***                       |
| Nr of LEDs        | 29 - SMD  |
| Working Temp.     | -20 to 40 °C  |
| Isolation         | Class III   |
| Protection degree | IP42  |
| Lumen maintenance | LM80 (Report available: <a href="#">LM-80 9000hrs</a> )   |
| Certificate       | CE / RoHs   |

\*Luminosity depreciation based on L70.

\*\*Beam angle: 50% of maximum lum.

\*\*\*Field angle: 10% of maximum lum.

## Light Technical Data:

| Reference   | Description  | Luminous flux (Lm)* | Efficiency (Lm/W) | Color Temp. (K)** | Color   | CRI > | Lens Type |
|-------------|--|---------------------|-------------------|-------------------|---------|-------|-----------|
| 11045032161 | LLED Barra 24V 47 WW303 HE ECO <sup>2</sup> DL Clear | 277                 | 96                | 3045 ± 84         | Warm    | 80    | Clear     |
| 11045032162 | LLED Barra 24V 47 WW303 HE ECO <sup>2</sup> DL Frost | 229                 | 79                | 3045 ± 84         | Warm    | 80    | Frost     |
| 11045034161 | LLED Barra 24V 47 NW403 HE ECO <sup>2</sup> DL Clear | 290                 | 100               | 3986 ± 144        | Neutral | 80    | Clear     |
| 11045034162 | LLED Barra 24V 47 NW403 HE ECO <sup>2</sup> DL Frost | 240                 | 83                | 3986 ± 144        | Neutral | 80    | Frost     |
| 11045025161 | LLED Barra 24V 47 CW503 ECO <sup>2</sup> DL Clear    | 263                 | 91                | 5029 ± 186        | Cool    | 80    | Clear     |
| 11045025162 | LLED Barra 24V 47 CW503 ECO <sup>2</sup> DL Frost    | 217                 | 75                | 5029 ± 186        | Cool    | 80    | Frost     |
| 11045036161 | LLED Barra 24V 47 CW573 HE ECO <sup>2</sup> DL Clear | 290                 | 100               | 5668 ± 207        | Cool    | 80    | Clear     |
| 11045036162 | LLED Barra 24V 47 CW573 HE ECO <sup>2</sup> DL Frost | 240                 | 83                | 5668 ± 207        | Cool    | 80    | Frost     |
| 11045027161 | LLED Barra 24V 47 CW653 ECO <sup>2</sup> DL Clear    | 263                 | 91                | 6536 ± 279        | Cool    | 80    | Clear     |
| 11045027162 | LLED Barra 24V 47 CW653 ECO <sup>2</sup> DL Frost    | 217                 | 75                | 6536 ± 279        | Cool    | 80    | Frost     |

\* Luminous flux ± 7.5%

\*\* Other color temperatures available upon request



## References Code:

The last six numbers are used to choose the options you desire.

### XXYYZZ

The XX refers to the body option.

The YY corresponds if the product have connectors.

The ZZ refers to the cable type.


### XX

Natural Aluminum | Ref:...01YYZZ

Chocolate Aluminum | Ref:...03YYZZ

White Aluminum | Ref:...02YYZZ

### YY



(STOPO) Top Input cable

Ref:...XX01ZZ



(1C2P STOPO) Top Input cable output connector

Ref:...XX08ZZ



(1C2P) Male connector input


Ref:...XX04ZZ



(1C2P) Male connector input female connector output

Ref:...XX06ZZ

### ZZ



(-)

Ref:...XXYY00



(ASQC2)

Ref:...XXYY27



(DCJ)

Ref:...XXYY25



(DC24)

Ref:...XXYY42

## Dimensions



| A (mm) | B (mm) | C (mm) | D (mm) | E (mm) | F (mm) | G (mm) |
|--------|--------|--------|--------|--------|--------|--------|
| 15     | 12     | 20     | 17     | 469    | 485    | 454    |

## CCT (Color temperature)

Color temperature tolerance of 3 SDCM MacAdam ellipses, defined by ANSI C78.377:2011

### Cool white 5000K 3SDCM



#### Photometric Parameters

EEL: 0.15 Energy Efficiency Class: A+ (EU 874-2012)

#### CIE Colorimetric Parameters

Chromaticity coordinates:  $x=0.3406$   $y=0.3498$   $u(u')=0.2090$   $v=0.3221$   $v'=0.4831$

CCT:  $T_c=5172K$  ( $duv=0.00096$ ) CRI:  $R_a=85.4$  Color Ratio:  $R=0.156$   $G=0.797$   $B=0.047$

### Cool white 6500K 3SDCM



#### Photometric Parameters

EEL: 0.15

Energy Efficiency Class: A+ (EU 874-2012)

#### CIE Colorimetric Parameters

Chromaticity coordinates:  $x=0.3147$   $y=0.3324$

$u(u')=0.1980$   $v=0.3136$   $v'=0.4704$

CCT:  $T_c=6374K$  ( $duv=0.00392$ )

CRI:  $R_a=87.8$


Color Ratio:  $R=0.140$   $G=0.802$   $B=0.058$

## Options


We provide all professionals and non professionals with a huge installation flexibility of our LED Bars.  
Give your lighting area a new look and design with 3 available finishing colours for the body lamp and 2 types of lens polycarbonate.  
Fixed or rotating docking.  
Huge connection flexibility.

### Options: Body

We provide 3 finishing jobs for the bar body, that allows for a new look and design when using our LED bars.



Natural Aluminum



Chocolate Aluminum



White Aluminum



Polycarbonate

### Options: Cover

We provide 2 types of polycarbonate, clear and frost.




Clear cover




Frost cover

### Options: Metallic Fixture


We provide 4 types of docking, rotating so the bar can be oriented, fixed @ 45°, fixed @ 180° and fixed @ 180° with extra 45°. Available in PVC, fixing at 180°, 45° and on corners.




Clip 180° (45° extra)



180° Fix clip




45° Fix clip




Rotating clip

### Options: Pvc Fixture


We provide 4 types of docking, rotating so the bar can be oriented, fixed @ 45°, fixed @ 180° and fixed @ 180° with extra 45°. Available in PVC, fixing at 180°, 45° and on corners.



180° PVC clip



45° PVC clip



Corner PVC clip

## Options: Connection

For greater installation flexibility of our LED bars, we provide bars with the following characteristics:

Cable input, connector input.

Cable input and connector output and connector input and connector output, so other LED bars can be interconnected.



Top Input cable  
(STopo)



Top Input cable output connector  
(1C2P STopo)



Male connector input  
(1C2P)



Male connector input female connector output  
(2C2P)



Top Input cable with ASQC2 connector  
(ASQC2)